

LIQUISCAN PL Metal separator for pumped products

- Detection and separation of metallic contaminations from pumped products – liquid or pasty
- Easy mounting with quick connections to vacuum fillers and pumps with nominal widths up to 100 mm
- Impressively small installation envelope
- Designed for easy cleaning in high-strength stainless steel
- Meets all IFS and HACCP requirements
- Outstanding ease of operation with product autolearn function and latest microprocessor technology





The LIQUISCAN PL pipeline metal separator is designed for inspecting liquid and paste products.

When metal is detected the valve reject mechanism removes the contaminant into a container. A variety of connectors is available to ensure easy integration in all types of conventional pipeline systems.



S+S Separation and Sorting Technology GmbH Regener Straße 130 D-94513 Schönberg Germany Tel. +49(0)8554 - 3080 Fax +49(0)8554 - 2606 info@se-so-tec.com www.se-so-tec.com

Reliable rejection of metal contaminants is guaranteed by the use of different types of valve depending on product characteristics.

The arc valve is ideally suited for all paste products. The air-operated ball valve is particularly useful in filling applications which contain coarser material.

Various pipe diameters are available depending on throughput.

LIQUISCAN PL metal separators are supplied on a stainless steel frame suitable for table or wall mounting. If required they are also available on a mobile, heightadjustable stand.



Separating system: Arc valve



LIQUISCAN PL with height-adjustable stand

LIQUISCAN PL metal separators are supplied with the GENIUS control unit for electronic evaluation and control. State-of-the-art microprocessor technology provides reliable digital signal processing with maximum resistance to interference (in accordance with strict EU guidelines). The GENIUS control unit is especially designed for automated processes and to meet the requirements of quality control systems.

(Further information: see "Control Units" brochure).



Separating system: Ball valve

Typical applications:

Inspection of jams, chocolate, soups, sauces etc between pump and filling station

For detailed information please request our technical data sheets or use the experience our S+S sales consultants.