

Compact Economical X-ray Inspection System for metallic, non-metallic, canned products



*Product Introduction:

Competitive price

Good sensitivity and stability

*Parameter

Model	TXE-1815	TXE-2815	TXE-3815
X-ray Tube	MAX. 80W/65kV		
Inspection Width	180mm	280mm	380mm
Inspection Height	150mm		
Best Inspection Ability	Stainless steel ball Φ 0.5mm Stainless steel wire Φ 0.3*2mm Glass/Ceramic ball Φ 1.5mm		
Conveyor Speed	5-90m/min		
O/S	Windows 7		
Protection Method	Soft curtain		
X-ray Leakage	< 1 μ Sv/h		
IP Rate	IP54 (IP65 Optional)		
Working Temperature	-10~40°C		0~40°C
Environment Humidity	30~90%, no dew		
Cooling Method	Industrial air conditioning		
Reject Mode	Sound and light alarm, belt stops (Rejecter optional)		
Air Pressure	0.8Mpa		
Power Supply	0.8kW		
Main Material	SUS304		
Surface Treatment	Brushed SUS		

*Note

The technical parameter above namely is the result of sensitivity by inspecting only the test sample on the belt. The actual sensitivity would be affected according to the products being inspected.

*Packing

*Factory Tour

Product

link :

<https://www.techigroup.com/compact-economical-x-ray-inspection-system-for-metallic-non-metallic-canned-products-product/>